

## **DECLARATION OF PERFORMANCE**

Nº 2013071210

1. Product-type:

HPL composite panel reference HYTEK (Thickness: 14 mm)

2. Name & contact address of the manufacturer:

COMPOSITES GUREA, S.A.

Zalain Auzoa, 13

31.780 Vera de Bidasoa (Spain)

3. Intended use of the construction product:

As internal finishes in floorings.

- 4. System of assessment and verification of the constancy of performance: 3
- 5. Notified body:
  - Tecnalia R&I Certificación NB 1239
  - Reaction to fire for initial type testing
  - System 3

6. Declared performance:

. Beciarea perrermanee.		
Essential characteristics	Performance	Harmonized technical specifications
Reaction to fire	B <sub>fl</sub> -S <sub>1</sub>	EN 14.041:2004
Contet of pentachloropenol	< 5 ppm	
Release of folmaldehyde	CLASS E1	
Water tightness	Water tight	
Slide resistance	DS	
Electric behaviur	Antiestatic	
Thermal conductivity	0,17 w /m * k	
Reaction to fire durability	NPD	

- The performance of the product identified in point 1 is in conformity with the declared performance in point 6
- This declaration performance is issued under the sole responsibility of the manufacturer identified in point 2
- Signed for and on behalf of the manufacturer by: Iñigo Rodrigo (General Director)

Signature: Place and date of issue:

Vera de Bidasoa August 25, 2015